





## ***New in the fleet!***

**JIBBI 1390 PRIMO, BIBI 1090-BL EVO, MULTILOADER 1.5FX**

*Working at height*



Free of emissions



Self-levelling



Non-marking tracks

# New in the fleet!

## JIBBI 1890 PRIMO, BIBI 1090-BL EVO, MULTILOADER 1.5FX Working at height

These machines can be operated completely electrically. All are equipped with non-marking tracks for work on difficult terrain. The scissor lift Bibi 1090 and the telescopic boom lift Jibbi 1890 are self-levelling which always ensures a stable and safe workplace.

The tracked transporter 1.5FX has a lifting capacity of 1,500 kg and can be controlled remotely.



Free of emissions



Self-levelling



Non-marking tracks

### Technical data

|                        | JIBBI 1890 Primo      | BIBI 1090-BL EVO               | Multiloader 1.5FX    |
|------------------------|-----------------------|--------------------------------|----------------------|
| Rental number          | 982862                | 981227                         | 654115               |
| Type                   | Electric crawler lift | Crawler scissor lift Bi-Energy | Electric multiloader |
| Working height (m)     | 17,90                 | 10,00                          | -                    |
| Platform height (m)    | 15,90                 | 8,00                           | -                    |
| Reach                  | 9,92                  | -                              | -                    |
| Platform capacity (kg) | 250                   | 300                            | 1.500                |
| Number of persons      | 2                     | 2                              | -                    |
| Platform rotation      | 70                    | -                              | -                    |
| Slope (°)              | 25                    | 25                             | 30                   |
| Weight (kg)            | 5.850                 | 2.960                          | 465                  |

### Dimensions

|                         |             |             |             |
|-------------------------|-------------|-------------|-------------|
| Length (m)              | 5,86        | 1,46        | 1,17        |
| Width (m)               | 2,20        | 2,18        | 0,70        |
| Height (m)              | 2,16        | 2,94        | 0,49        |
| Platform dimensions (m) | 1,80 x 0,70 | 1,80 x 1,30 | 0,69 x 1,10 |

### Energy source

|         |                   |                   |                      |
|---------|-------------------|-------------------|----------------------|
| Drive   | Electric          | Bi-energy         | Electric             |
| Engine  | -                 | Kubota diesengine | -                    |
| Battery | Lithium 440AH-48V | Lithium 100Ah-48V | AGM battery 55Ah-48V |
| Charger | 230V, 65AH        | 230V, 20Ah        | 230V, 7,5Ah          |



- Non-marking caterpillars
- High platformcapacity
- Jib arm (1890 Primo, BIBI 1090)
- Radio controlled (1.5FX)
- Self-levelling

